



## FICHA TECNICA DE PRODUCTO

### GRILLETE RECTO (CADENA) PASADOR ROCADO MOD G-210



- FORJADOS – TEMPLADOS Y REVENIDOS, CON PERNOS DE ALEACION
- ACERO GALVANIZADO POR INMERSION EN CALIENTE.
- FABRICADO SEGÚN NORMAS ASME B30.26

		MEDIDAS (plg)												
COD	MEDIDA	WLL (ton)	A	B	C	D	E	F	G	K	L	M		
2635	1/4"	0.50	0.47	0.31	0.25	0.25	0.97	0.61	0.88	1.59	0.19	1.38		
2646	5/16"	0.75	0.53	0.38	0.31	0.31	1.16	0.75	1.03	1.91	0.22	1.66		
2644	3/8"	1.00	0.66	0.44	0.38	0.38	1.41	0.91	1.25	2.3	0.25	2.03		
2654	7/16"	1.50	0.75	0.50	0.44	0.44	1.63	1.06	1.44	2.66	0.31	2.38		
2633	1/2"	2.00	0.81	0.63	0.50	0.50	1.81	1.19	1.63	3.03	0.38	2.69		
2651	5/8"	3.25	1.06	0.08	0.62	0.63	2.31	1.50	2.00	3.75	0.44	3.34		
2643	3/4"	4.75	1.25	0.88	0.81	0.75	2.75	1.81	2.38	4.53	0.5	3.97		
2661	7/8"	6.50	1.44	1.00	0.97	0.88	3.19	2.09	2.81	5.33	0.5	4.5		
2698	1"	8.50	1.69	1.13	1.00	1.00	3.69	2.38	3.19	5.94	0.56	5.07		
2630	1 1/8"	9.50	1.81	1.25	1.25	1.13	4.06	2.69	3.58	6.78	0.63	5.59		
2629	1 1/4"	12.00	2.03	1.38	1.38	1.25	4.53	3.00	3.94	7.5	0.69	6.16		
2632	1 3/8"	13.50	2.25	1.50	1.50	1.38	5.01	3.31	4.38	8.28	0.75	6.84		
2627	1 1/2"	17.00	2.38	1.63	1.62	1.50	5.38	3.62	4.81	9.06	0.81	7.35		
2631	1 3/4"	25.00	2.88	2.00	2.12	1.75	6.38	4.19	5.75	10.97	1	9.08		
2637	2"	35.00	3.25	2.25	2.00	2.00	7.25	4.81	6.75	12.28	1.22	10.34		
6537	2 1/2"	55.00	4.13	2.75	2.62	2.62	9.38	5.69	8.00	14.84	1.38	13		
2642	3"	85.00												

FACTOR DE SEGURIDAD 6:1